



Part #	Stand-Off	Height
BA 602-8	1/2"	3-1/2"
BA 603-8	1-1/2"	4-1/2"
BA 602-12	1/2"	3-1/2"
BA 603-12	1-1/2"	4-1/2"
BA 602-16	1/2"	3-1/2"
BA 603-16	1-1/2"	4-1/2"

CONSTRUCTION, TESTING, SEAMING

- G-90 Galvanized 50ksi Steel Coating
- Centering Tang:
 - Fixed at center for installation
 - Free thermal movement after installation
- UL 90 Approved: Construction # 552, 552A and 552B
- ASTM E 1592 Wind Uplift Tested
- Three mechanical Seaming Options: RollLok®, TripleLok® and QuadLok®

THERMAL MOVEMENT

Clip Part #	Tab Length	Slide One Way	Maximum Length Plane Without Expansion Design		
			Temp Diff 100 degrees	Temp Diff 125 degrees	Temp Diff 150 degrees
MPS 60X -8	8"	2.375	305' - 0"	245' - 0"	200' - 0"
MPS 60X -12	12"	3.90	500' - 0"	410' - 0"	340' - 0"
MPS 60X -16	16"	3.90	500' - 0"	410' - 0"	340' - 0"



The Superior Seam Technology design and engineering meets the more stringent corner/edge zones uplift codes.